



US009636234B2

(12) **United States Patent**
Gfeller et al.

(10) **Patent No.:** **US 9,636,234 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **HYBRID INTERVERTEBRAL DISC SPACER
DEVICE AND METHOD OF
MANUFACTURING THE SAME**

(58) **Field of Classification Search**

CPC A61F 2/442; A61F 2/4455; A61F 2/4465
See application file for complete search history.

(71) Applicant: **DePuy Synthes Products, Inc.,**
Raynham, MA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,171,281 A 12/1992 Parsons et al.
6,569,201 B2 5/2003 Moumene et al.
(Continued)

(72) Inventors: **Andreas Gfeller**, Basel (CH); **Dirk
Dittmann**, Nunningen (CH); **Salman
Chegini**, Bern (CH); **Phillippe
Lindenmann**, Basel (CH)

(73) Assignee: **DePuy Synthes Products, Inc.,**
Raynham, MA (US)

OTHER PUBLICATIONS

Eisner, W., "Orthofix Launches Hybrid PEEK/Titanium Spacer",
Orthopedics This Week, www.ryortho.com, Jan. 14, 2013.

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

Primary Examiner — David Bates

Assistant Examiner — Olivia C Chang

(21) Appl. No.: **14/964,413**

(74) *Attorney, Agent, or Firm* — Nutter McClennen &
Fish LLP

(22) Filed: **Dec. 9, 2015**

(65) **Prior Publication Data**

US 2016/0089250 A1 Mar. 31, 2016

Related U.S. Application Data

(63) Continuation of application No. 13/804,586, filed on
Mar. 14, 2013, now Pat. No. 9,238,319.

(51) **Int. Cl.**

A61F 2/44 (2006.01)

B29C 45/14 (2006.01)

B29L 31/00 (2006.01)

B29K 705/00 (2006.01)

A61F 2/30 (2006.01)

B29K 71/00 (2006.01)

B29K 305/02 (2006.01)

(52) **U.S. Cl.**

CPC **A61F 2/4465** (2013.01); **A61F 2/4455**
(2013.01); **B29C 45/14311** (2013.01);

(Continued)

(57)

ABSTRACT

A hybrid spinal implant device, and method of making the same are disclosed. The spinal implant device comprises two facing endplates, each having at least one anchoring wall or pin element, and a plastic spacer anchored to and located between the two endplates. The endplates may be manufactured from titanium. The plastic spacer may be manufactured from a radiolucent, and bio-compatible polymer-based material including polyetheretherketone ("PEEK"), polyetherketone, polyetherketoneketone, and/or fiber reinforced plastic. The endplates made of titanium allow for enhanced bone growth, while the plastic/PEEK spacer element allows for improved load absorption and distribution. The spinal implant device, using titanium endplates and a PEEK spacer, provides excellent radiolucency thereby eliminating the need for X-ray markers either intra- or post-operation. The manufacturing method for the hybrid spinal implant device uses injection molding to insert or back injection mold the spacer between the two endplates.

17 Claims, 7 Drawing Sheets

